


IS 15683



CM/L-3985085



Check 3D Hologram
on Fire Extinguisher

Water

Stored Pressure Fire Extinguisher



FEATURES

- Stunning looks & Design
- High Quality Powder Coating
- Squeeze Valve for easy to use
- ISI Marked

SUITABLE FOR CLASSES OF FIRE



Wood, Paper, Cloth, Jute, Plastic & Etc.

Water, the best fire extinguishant suited for combating fires involving ordinary carbonaceous materials like wood, paper, cloth, rubber & jute. Water extinguishes fire rapidly by striking, instant cooling & quenching effects.

TECHNICAL DATA

MODEL	FEW9
Capacity (In Ltrs.)	9
Fire Rating	3A
Average Discharge Time	25 sec
Height (Approx.)	60 cm
Diameter (Approx)	175 mm
Gross Weight (Approx.)	12.5 Kgs
Operating Temperature Range	+5°C TO +55°C
Service Pressure	15 Bar
Maximum Service Pressure	16 Bar
Test Pressure	35 Bar
Certification	BIS (ISI)

Firestop fire extinguishers are guaranteed against any manufacturing defects.
Design & specification may be changed without notice in view of technical upgradation.



Firestop
coz Life is Priceless

Log on to
www.firestopgroup.com

Email
contact@firestopgroup.com

Tel : Number
+91 79-22161962

Tel Fax
+91-79-22173963

Firestop Engineers

20, Amarnath Indl. Estate,
Old Manek Chowk Mill Compound,
Near Idgah Chowki,
Ahmedabad-16 - Gujarat India

IS 15683



CM/L-3985085



Check 3D Hologram
on Fire Extinguisher



Stored Pressure Fire Extinguisher



This extinguisher forms a thick layer of foam over the burning surface, effectively cutting of atmospheric supply of oxygen to the burning surface thereby smothering the fire and preventing re-ignition. Foam extinguishes fire by giving blanketing effect.

FEATURES

- AFFF Agent to combat A & B Class Fires
- Stunning looks & Design
- High Quality Powder Coating
- Squeeze Valve for easy to use
- High Quality Nozzle for Effective fire fighting
- ISI Marked

SUITABLE FOR CLASSES OF FIRE



Wood, Paper, Cloth,
Jute, Plastic & Etc.



Oil, Petrol, Diesel,
Paints, Solvents & Etc.

TECHNICAL DATA

MODEL	FEF9
Capacity (In Ltrs.)	9
Fire Rating	4A & 34B
Average Discharge Time	28 sec
Height (Approx.)	60 cm
Diameter (Approx)	175 mm
Gross Weight (Approx.)	12.5 Kgs
Operating Temperature Range	+5°C TO +55°C
Service Pressure	15 Bar
Maximum Service Pressure	16 Bar
Test Pressure	35 Bar
Certification	BIS (ISI)

Firestop fire extinguishers are guaranteed against any manufacturing defects.
Design & specification may be changed without notice in view of technical upgradation.



Firestop
coz Life is Priceless

Log on to
www.firestopgroup.com

Email
contact@firestopgroup.com

Tel : Number
+91 79-22161962

Tel Fax
+91-79-22173963

Firestop Engineers

20, Amarnath Indl. Estate,
Old Manek Chowk Mill Compound,
Near Idgah Chowki,
Ahmedabad-16 - Gujarat India

IS 15683



CM/L-3985085



Check 3D Hologram
on Fire Extinguisher



Powder

Stored Pressure Fire Extinguisher

A premium range of appliances available in MAP Base (ABC) Powder pressurised with dry nitrogen gas. MAP Base Powder is one of the most versatile & highly effective agents suitable for combatting fires involving wood, inflammable liquids, gases & electrical wiring. This Extinguisher knocks down fire by beating & displacement of air.



FEATURES

- MAP Base Powder to combat all fires
- Available in 5 capacities
- Stunning looks & Design
- High Quality Powder Coating
- Squeeze Valve for easy to use
- ISI Marked

SUITABLE FOR CLASSES OF FIRE



Wood, Paper, Cloth,
Jute, Plastic & Etc.



Oil, Petrol, Diesel,
Paints, Solvents & Etc.



LPG, Acetylene Gas,
Industrial Gases & Etc.



Electrical Energized
Machines

TECHNICAL DATA

MODEL	FEP1	FEP2	FEP4	FEP6	FEP9
Capacity (In Kgs.)	1	2	4	6	9
Fire Rating	1A & 8B	1A & 13B	2A & 21B	3A	4A
Average Discharge Time	9 sec	13 sec	18 sec	20 sec	26 sec
Height (Approx.)	34.00 cm	37.00 cm	48 cm	59 cm	60 cm
Diameter (Approx.)	86.5 mm	108 mm	130 mm	150 mm	175 mm
Gross Weight (Approx.)	2 Kgs	3.5 Kgs	6.5 Kgs	9 Kgs	14 Kgs
Operating Temperature Range	-10°C TO +55°C				
Service Pressure	15 Bar				
Maximum Service Pressure	16.5 Bar				
Test Pressure	35 Bar				
Certification	BIS (ISI)				

Firestop fire extinguishers are guaranteed against any manufacturing defects.
Design & specification may be changed without notice in view of technical upgradation.



Firestop
coz Life is Priceless

Log on to
www.firestopgroup.com

Email
contact@firestopgroup.com

Tel : Number
+91 79-22161962

Tel Fax
+91-79-22173963

Firestop Engineers

20, Amarnath Indl. Estate,
Old Manek Chowk Mill Compound,
Near Idgah Chowki,
Ahmedabad-16 - Gujarat India

Fire Extinguisher



The quick & efficient flame knockdown property of CO₂ gas makes it ideal for tackling fires involving inflammables liquids like petrol, oil, paints, solvents and industrial gases. It is also suitable for sophisticated machineries. CO₂ extinguishes the fire within seconds by dilution of oxygen and chilling effect.

Note : Check 3D Hologram on Firestop Fire Extinguishers for Genuineness.

FEATURES

- Pure High Grade CO₂ Gas
- Available in 2 capacities
- Stunning looks & design
- ISI Marked

SUITABLE FOR CLASSES OF FIRE



PERFORMANCE DATA

MODEL	FEC2	FEC4
Capacity (In Kgs.)	2	4.5
Fire Rating	13B	34B
Average Discharge Time	10 sec	17 sec
Height (Approx.)	58.00 cm	70 cm
Diameter (Approx)		
Gross Weight (Approx.)	8 Kgs	16 Kgs
Operating Temperature Range	-10°C TO +55°C	
Service Pressure	55 Bar	
Maximum Service Pressure	90 Bar	
Test Pressure	250 Bar	
Certification	BIS (ISI)	

Firestop fire extinguishers are guaranteed against any manufacturing defects.
 Design & specification may be changed without notice in view of technical upgradation.



Check 3D Hologram
on Fire Extinguisher



Clean Agent

Stored Pressure Fire Extinguisher



Clean Agent extinguishers have effective extinguishing action, environmentally acceptable and excellent alternative for Halon 1211. Clean Agent is a non corrosive, electrically non conductive and free of residue. It is ideally suited for protecting high value equipments.

FEATURES

- HFC236FA Clean Agent Gas
- Available in 4 capacities
- Stunning looks & Design
- Best suited for vital machines
- Squeeze Valve for easy to use
- No residue

SUITABLE FOR CLASSES OF FIRE



Wood, Paper, Cloth,
Jute, Plastic & Etc.



Oil, Petrol, Diesel,
Paints, Solvents & Etc.



LPG, Acetylene Gas,
Industrial Gases & Etc.



Electrical Energized
Machines

TECHNICAL DATA

MODEL	FECA1	FECA2	FECA4	FECA6
Capacity (In Kgs.)	1	2	4	6
Average Discharge Time	11 sec	12 sec	14 sec	20 sec
Height (Approx.)	315mm	390mm	500mm	530mm
Diameter (Approx.)	86.5 mm	108 mm	130 mm	150 mm
Gross Weight (Approx.)	2 Kgs	3.5 Kgs	6.5 Kgs	9 Kgs
Operating Temperature Range	-10°C TO +55°C			
Service Pressure	15 Bar			
Maximum Service Pressure	16.5 Bar			
Test Pressure	35 Bar			
Content	HFC236FA Clean Agent Gas			
Propellant	Nitrogen			

Firestop fire extinguishers are guaranteed against any manufacturing defects.
Design & specification may be changed without notice in view of technical upgradation.



Firestop
coz Life is Priceless

Log on to
www.firestopgroup.com

Email
contact@firestopgroup.com

Tel : Number
+91 79-22161962

Tel Fax
+91-79-22173963

Firestop Engineers

20, Amarnath Indl. Estate,
Old Manek Chowk Mill Compound,
Near Idgah Chowki,
Ahmedabad-16 - Gujarat India



Check 3D Hologram
on Fire Extinguisher



ABC Modular

Automatic Fire Extinguisher



Firestop presents Modular type ABC Powder Automatic Fire Extinguisher which keeps guard round-the-clock and extinguishes fire quickly and efficiently especially in close places where fire could cause extensive damage if not detected and extinguished in time. Automatic, hence no human involvement, reducing the chances of injury and accidents to virtually zero.

FEATURES

- Automatic Round-the-Clock Protection
- MAP Base Powder to combat all fires
- Available in 2 capacities
- Stunning looks & Design
- High Quality Powder Coating
- Rechargeable & easy to service

SUITABLE FOR CLASSES OF FIRE



Wood, Paper, Cloth,
Jute, Plastic & Etc.



Oil, Petrol, Diesel,
Paints, Solvents & Etc.



LPG, Acetylene Gas,
Industrial Gases & Etc.



Electrical Energized
Machines

TECHNICAL DATA

MODEL	FEMP2	FEMP5
Capacity (In Kgs.)	2	5
Volume Protection	3m ³	8m ³
Area Protection	1 to 1.5 m ²	3.5 to 4 m ²
Average Discharge Time	8-10 sec	10-15 sec
Hanging Vertically	1.5m	1.5 to 2m
Service Pressure	15 Kgf/cm ²	
Test Pressure	35 Kgf/cm ²	
Propellant	Nitrogen	
Content	Mono Ammonium Phosphate Base Powder	
Fusible Bulb	68°	

Firestop fire extinguishers are guaranteed against any manufacturing defects.
Design & specification may be changed without notice in view of technical upgradation.



Firestop
coz Life is Priceless

Log on to
www.firestopgroup.com

Email
contact@firestopgroup.com

Tel : Number
+91 79-22161962

Tel Fax
+91-79-22173963

Firestop Engineers

20, Amarnath Indl. Estate,
Old Manek Chowk Mill Compound,
Near Idgah Chowki,
Ahmedabad-16 - Gujarat India



Clean Agent Modular

Automatic Fire Extinguisher



Check 3D Hologram
on Fire Extinguisher



Firestop presents Modular type Clean Agent Automatic Fire Extinguisher which keeps guard round-the-clock and extinguishes fire quickly and efficiently especially in close places where fire could cause extensive damage if not detected and extinguished in time. Automatic, hence no human involvement, reducing the chances of injury and accidents to virtually zero.

FEATURES

- Automatic Round-the-Clock Protection
- Effective for sophisticated & vital machines
- Available in 2 capacities
- Stunning looks & Design
- No residue
- Eco-Friendly

SUITABLE FOR CLASSES OF FIRE



Wood, Paper, Cloth,
Jute, Plastic & Etc.



Oil, Petrol, Diesel,
Paints, Solvents & Etc.



LPG, Acetylene Gas,
Industrial Gases & Etc.



Electrical Energized
Machines

TECHNICAL DATA

MODEL	FEMCA2	FEMCA5
Capacity (In Kgs.)	2	5
Volume Protection	3m ³	8m ³
Area Protection	1 to 1.5 m ²	3.5 to 4 m ²
Average Discharge Time	8-10 sec	10-15 sec
Hanging Vertically	1.5m	1.5 to 2m
Service Pressure	15 Kgf/cm ²	
Test Pressure	35 Kgf/cm ²	
Propellant	Nitrogen	
Content	Clean Agent Gas HFC236FA	
Fusible Bulb	68°	

Firestop fire extinguishers are guaranteed against any manufacturing defects.
Design & specification may be changed without notice in view of technical upgradation.



Firestop
coz Life is Priceless

Log on to
www.firestopgroup.com

Email
contact@firestopgroup.com

Tel : Number
+91 79-22161962

Tel Fax
+91-79-22173963

Firestop Engineers

20, Amarnath Indl. Estate,
Old Manek Chowk Mill Compound,
Near Idgah Chowki,
Ahmedabad-16 - Gujarat India